

**GRAPHICS** - Overlaminating Films

Issue date : 05/01/2005 Date last modification : 22/05/2020

# 4-GL3B-01346 RI-121/200 FLOOR TALKER CLEAR AP906 PERMANENT WG90

# Face Material

Clear embossed scuff resistant vinyl.

Type Colour and Finish Weight Thickness Embossed vinyl Clear 268 g/m<sup>2</sup> ±10% ISO-536 200 µ ±10% ISO 534-80

# <u>Adhesive</u>

Solvent based permanent acrylic adhesive featuring good water and cleaning agents resistance. High adhesion on a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

Reference Type Min. Appl. Temp. Service Temp. Shear Tack Final Adhesion AP906 permanent Acrylic permanent +10°C -20°C/+140°C Very high High N/inch<sup>2</sup> Very high N/inch

#### Liner

Туре	One side siliconised Glassine	
Colour and Finish	White	
Weight	90 g/m² ±10%	PP-032 - ISO 536
Thickness	77 µ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

## Applications

Floor talker overlaminating film.

- . Flammability: Self extinguish (ISO-3795)
- . Slip resistance: classified R10 according to DIN 51130:2014
- . Outdoor exposure durability: up to 3 MONTHS.
- . System (film+overlaminate) for application strictly on smooth surfaces or smooth concrete.

## Printing Methods

Not printable.

Testing for suitability between media, printers and inks is always recommended prior to use.

### Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of  $~22^\circ C$   $\pm~2^\circ C$  and 50  $\pm~5\%$  of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



Ritrama S.p.A. Via Senatore Simonetta, 24 20867 Caponago (MB) ITALY e-mail:info@ritrama.com w w w . r i t r a m a . c o m

