

Technical Data Sheet

Issue date: 27/10/2014 Date last modification: 27/10/2014

# **GRAPHICS** - PROMOTIONAL

## 08132 - RI-143/80 PVC GLOSS WHITE AP940 WK120 RIT/GRY

### Face Material

Gloss white monomeric vinyl film.

Type Monomeric vinyl Colour and Finish Gloss white

## **Adhesive**

Acrylic permanent adhesive featuring high clarity and very high cohesion. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for applar surfaces (like PE and PP).Suitable for application at low temperature

Reference AP 940 Permanent Type Acrylic permanent

Min. Appl. Temp. +5 °C

Service Temp. -30°C/+120°C

Shear High
Tack 8 N/inch²
Final Adhesion 13 N/inch

#### Liner

Type One side siliconised clay coated

Kraft

Colour and Finish White

Weight 120 g/m<sup>2</sup> PP-032 - ISO

±10% 536

Thickness 125  $\mu$  ±10% ISO 534 Transparency n.a. % DIN 53 147-64

## **Applications**

For promotional graphics and point of sale advertising with medium outdoor durability where is requested an higher opacity of the film

## **Printing Methods**

Solvent and eco-solvent ink-jet printing. The RI-JET series of ink jet print media give excellent print results with UV ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.

Testing for suitability between media, printers and inks is always recommended prior to use.

## Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of  $22^{\circ}\text{C} \pm 2^{\circ}\text{C}$  and 50  $\pm$  5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

All information is subject to change without prior notice.





