



Product code: 4-GL1B-01287

APPLICATION TAPE 200 PAPER

A complete range of self-adhesive solutions for lamination and application of all large format digital materials printed with the main types of ink: solvent, UV, eco-solvent and Latex and UV ink-jet. Application tape to allow the media transfer easily.

Applications

Self-wound application tape offering clean removability without adhesive stringing. Excellent for lifting and transferring graphic, included printed, of all sizes.

Face Material

Paper based application tape

Type	Paper	
Colour and Finish	White	
Weight	80 g/m ² ±10%	ISO-536
Thickness	80 µm ±10%	ISO 534-80

Adhesive

High tack rubber based adhesive.

Type	Rubber based	
Min. Appl. Temp.	10 °C	
Service Temperature	+10°C/+80°C	
Shear	High	FINAT FTM8
Tack	14 N/25mm	FINAT FTM9

Printing Methods

Not-printable

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the storage conditions as defined by FINAT section 2.5:

- Ideal storage conditions are at a temperature of 20 -25 °C and 40 - 50 % HR.
- Store in a cool and dry place.
- Do not store close to a heat source or in direct sunlight.
- Keep the material in the original packaging until required for use.

Pay particular attention to the recommended shelf-life and ensure correct stock rotation.

Disclaimer

All Ritrama's products are subject to manufacturing controls in order to guarantee the good quality of the products. The statements, technical information, data, values and recommendations regarding Ritrama's products are based on research and tests we believe to be reliable, but do not constitute a guarantee or warranty of whatsoever nature.

Considering the multiple uses of Ritrama's products, the user is recommended to test the products prior to their use, so to determine and ascertain the suitability and performance of the product for its intended application and purpose.

The methods of conversion and application of Ritrama's self-adhesive materials are multiple and it is therefore essential that the users are aware of the particular method to be used, prior to commencing the production.

Printing: Testing for compatibility between product, printers and inks is always highly recommended before printing the product.

Application Systems and Conditions: it is recommended that the performance of the product be always tested in the actual applications conditions as substrate state (rough, smooth, flat or irregular shapes, moderate curves, with or without rivets); applicator technology (hand application or fully automated lines); specific stress on Ritrama material once applied (high and/or low temperature, mechanical stress, exposure to challenging environment conditions), et cetera.

As Ritrama's products are used in conditions beyond its control, such as those listed above as example, Ritrama does not assume any liability for inappropriate use of the products.

Ritrama reserves the right to modify at any time and without the need of a prior notice, at its sole and exclusive discretion, the products, their features and technical specifications.

All Ritrama's products are sold subject to Ritrama's general terms and conditions of sale listed in the following Ritrama's web page: <http://www.ritrama.com/en/sale-conditions/>