

Product code: 4-GL3B-07361

RI-JET 150 STATIC GLOSS WHITE

A complete range of static vinyl solutions for indoor windows, fairs and events.

All our self-adhesive materials are suitable for the main large format digital printing techniques: solvent, eco-solvent, Latex and UV ink-jet to meet all market requirements.

Applications

For use in advertising specialties such as retail window signage and promotional displays and novelty stickers. This product is fully REACH compliant and does not contain phthalate plasticisers. It conforms to European Toy Standard EN71 part 3.

Face Material

Gloss white plasticised static cling vinyl.

Type	Static cling vinyl	
Colour and Finish	Gloss white	
Weight	202 g/m ² ±10%	ISO-536
Thickness	150 µm ±10%	ISO 534-80
Dimensional stability	< 0.5 %	ASTM D1204
Tensile Strength MD	> 15 N/mm ²	ASTM D882
Tensile Strength CD	> 15 N/mm ²	ASTM D882
Elongation at break MD	> 200 %	ASTM D882
Elongation at break CD	> 200 %	ASTM D882
Flammability	SELF-EXTINGUISH	ISO 3795:1989
Outdoor vertical exposure durability	UP TO 6 MONTHS	

Printing Methods

This product gives excellent print results with UV and solvent screenprinting, solvent and eco solvent, UV and latex ink jet printing. There are high levels of plasticiser in this type of PVC, which can lead to cosmetic imperfections and poor ink key, which is very much dependent on the type of ink used, the colour of the ink and colour density: very light coverage and light colours are most susceptible combinations for print related issues.

Shelf life

6 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the storage conditions as defined by FINAT section 2.5:

- Ideal storage conditions are at a temperature of 20 -25 °C and 40 - 50 % HR.
- Store in a cool and dry place.
- Do not store close to a heat source or in direct sunlight.
- Keep the material in the original packaging until required for use.

Pay particular attention to the recommended shelf-life and ensure correct stock rotation.

Disclaimer

All Ritrama's products are subject to manufacturing controls in order to guarantee the good quality of the products. The statements, technical information, data, values and recommendations regarding Ritrama's products are based on research and tests we believe to be reliable, but do not constitute a guarantee or warranty of whatsoever nature.

Considering the multiple uses of Ritrama's products, the user is recommended to test the products prior to their use, so to determine and ascertain the suitability and performance of the product for its intended application and purpose.

The methods of conversion and application of Ritrama's self-adhesive materials are multiple and it is therefore essential that the users are aware of the particular method to be used, prior to commencing the production.

Printing: Testing for compatibility between product, printers and inks is always highly recommended before printing the product.

Application Systems and Conditions: it is recommended that the performance of the product be always tested in the actual applications conditions as substrate state (rough, smooth, flat or irregular shapes, moderate curves, with or without rivets); applicator technology (hand application or fully automated lines); specific stress on Ritrama material once applied (high and/or low temperature, mechanical stress, exposure to challenging environment conditions), et cetera.

As Ritrama's products are used in conditions beyond its control, such as those listed above as example, Ritrama does not assume any liability for inappropriate use of the products.

Ritrama reserves the right to modify at any time and without the need of a prior notice, at its sole and exclusive discretion, the products, their features and technical specifications.

All Ritrama's products are sold subject to Ritrama's general terms and conditions of sale listed in the following Ritrama's web page: <http://www.ritrama.com/en/sale-conditions/>